

# Stress field and strut-and tie models

Miguel Fernández Ruiz

Universidad Politécnica de Madrid



EUROCODES

EN 1992

Design  
of concrete  
structures

2<sup>nd</sup> generation of Eurocode 2 on concrete structures

Madrid, October 17<sup>th</sup>, 2023



# 1. Introduction

## Stress Fields and Strut-and-Tie Models as a Basic Tool for Design and Verification in Second Generation of Eurocode 2

### Campos de tensiones y modelos de bielas y tirantes: herramientas fundamentales para el proyecto y comprobación de estructuras de hormigón en la segunda generación del Eurocódigo 2

Miguel Fernández Ruiz<sup>a</sup>, Linh Cao Hoang<sup>b</sup>, Aurelio Muttoni<sup>c</sup>

<sup>a</sup> Professor, Universidad Politécnica de Madrid, Spain

<sup>b</sup> Professor, Danmarks Tekniske Universitet, Denmark

<sup>c</sup> Professor, Ecole Polytechnique Fédérale de Lausanne, Switzerland

Recibido el 1 de julio de 2022; aceptado el 2 de noviembre de 2022

#### ABSTRACT

Within the frame of the revision of the Eurocode 2 for concrete structures, the section devoted to strut-and-tie design has been updated to enhance its applicability, its consistency with other sections and its ease-of-use. As a result, a number of changes have been introduced. Namely, the use of stress fields and their combination with classical strut-and-tie models has been incorporated. The changes in this section can be seen as an effort to provide a more comprehensive and general tool for designers, that can be transparently applied to any structural member with sufficient reinforcement for crack control. In this paper, the consistency between the strut-and-tie and the stress field methods is clarified as well as the fundamentals of the revision performed in Eurocode 2. The paper also elaborates how the code can be used for advanced analyses, considering in an explicit manner the compatibility of deformations to obtain refined estimates of the structural resistance.

**KEYWORDS:** Strut-and-tie, stress fields, limit analysis, shear, discontinuity regions, shell design.

©2023 Hormigón y Acero, the journal of the Spanish Association of Structural Engineering (ACHE). Published by Cinter Divulgación Técnica S.L. This is an open-access article distributed under the terms of the Creative Commons (CC BY-NC-ND 4.0) License

#### RESUMEN

En el marco de la revisión del Eurocódigo 2 para estructuras de hormigón, se ha actualizado el capítulo dedicado al diseño mediante modelos de bielas y tirantes, mejorando su coherencia con otras secciones así como su facilidad de uso. Para ello, se han introducido una serie de cambios, como la consideración del método de campos de tensiones y su combinación con los modelos clásicos de bielas y tirantes. Estos cambios pueden considerarse como un esfuerzo para proporcionar una herramienta más completa y general. En este artículo, se clarifica la coherencia entre los métodos de bielas y tirantes y los campos de tensiones, así como los principios de la revisión efectuada para el Eurocódigo 2. También se explica cómo puede utilizarse dicha norma para realizar análisis avanzados, considerando de manera explícita la compatibilidad de deformaciones con el objetivo de obtener estimaciones precisas de la resistencia.

**PALABRAS CLAVE:** Bielas y tirantes, campos de tensiones, análisis límite, cortante, regiones de discontinuidad, diseño de lajas.

©2023 Hormigón y Acero, la revista de la Asociación Española de Ingeniería Estructural (ACHE). Publicado por Cinter Divulgación Técnica S.L. Este es un artículo de acceso abierto distribuido bajo los términos de la licencia de uso Creative Commons (CC BY-NC-ND 4.0)

#### 1.

#### INTRODUCTION

Reinforced concrete as a structural material was introduced at the end of the 19th century through a number of patents [1-3].

<sup>a</sup> Persona de contacto / Corresponding author:  
Correo-e / e-mail: [miguel.fernandezruiz@upm.es](mailto:miguel.fernandezruiz@upm.es) (Miguel Fernández Ruiz).

How to cite this article: Fernández Ruiz, M., Hoang, L.C., & Muttoni, A. (2023) Stress Fields and Strut-and-Tie Models as a Basic Tool for Design and Verification in Second Generation of Eurocode 2, *Hormigón y Acero* 74(299-300):79-90, doi: <https://doi.org/10.33386/hsa.2022.3086>

Almost from the beginning, the engineers realised that traditional design methods rooted in linear elastic theory could not adequately be used to explore the full potential of the new composite material. A new approach was therefore needed and within

respect (at nodes A and C) the minimum angle  $\theta_{cr} = 20^\circ$  recommended by the PrEN1992-1-1:2022.

Grounded on these observations, some refinements can be introduced in the strut-and-tie model, Figure 9e, by providing spreading of the struts. Such spreading allows fulfilling the requirements in terms of minimum angles between struts and ties, and needs the arrangement of additional reinforcement in the form of horizontal and vertical bars (stirrups or pins, see Figure 9f). With respect to the region at the right of the bent of the bar, the fan region (with a steeper angle of the resulting strut) and the constant-angle compression field region (with a flatter angle of the resulting strut) can be designed following the standard procedure for shear in members with transverse reinforcement.

Finally, detailed checks can be performed on the basis of stress fields at the critical regions (nodal regions A and B), ensuring that sufficient space is available for development of the struts and nodal regions. To that aim, a constant and safe value of the efficiency factor is adopted ( $\nu = 0.55$  ac-

counting for the angles of the struts and ties), allowing to analyse all nodes under plane-stress hydrostatic conditions, see Figure 9f. The results show that this aspect is not critical. Also, detailing of the reinforcement can be consistently established, in terms of type of reinforcement and anchorage lengths.

For a final optimisation, or in case the performance of the detailed needed to be assessed, a refined EPFS analysis could also be performed. The results are shown in Figure 10 for two cases. The first considers only inclined reinforcement and stirrups at the right of the bend (Figure 10a-d), corresponding to the reinforcement layout of Figure 9d. The latter considers also an additional horizontal and vertical reinforcement in the discontinuity region (Figures 10e-h), corresponding to the reinforcement layout of Figure 9f. In all cases, the load was applied by means of a stiff plate, distributing it into the concrete surface.

When only inclined reinforcement is provided in the discontinuity region (Figures 10a-d), a similar response to that of Figure 9d results, with an inclined compression field devel-




Figure 9. Example of application: (a) element investigated; (b) critical detail; (c) analysis based on thrust line; (d) strut-and-tie model (with lines for analysis with graphic statics shown in light grey); (e) refined strut-and-tie model; (f) stress field verifications and reinforcement layout; and (g) enhanced detailing.

# 1. Introduction

EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM

EN 1992-1-1

December 2004

ICS 91.010.30; 91.080.40

Supersedes ENV 1992-1-1:1991, ENV 1992-1-3:1994,  
ENV 1992-1-4:1994, ENV 1992-1-5:1994, ENV 1992-1-  
6:1994, ENV 1992-3:1999

English version

## Eurocode 2: Design of concrete structures - Part 1-1: General rules and rules for buildings

Eurocode 2: Calcul des structures en béton - Partie 1-1:  
Règles générales et règles pour les bâtiments

Eurocode 2: Bemessung und konstruktion von Stahlbeton-  
und Spannbetontragwerken - Teil 1-1: Allgemeine  
Bemessungsregeln und Regeln für den Hochbau

This European Standard was approved by CEN on 16 April 2004.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHE KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

© 2004 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.

Ref. No. EN 1992-1-1:2004

Project NDP - working copy

EN 1992-1-1:2004 (E)

(5) Where proprietary products are used as shear reinforcement,  $V_{Rd,cs}$  should be determined by testing in accordance with the relevant European Technical Approval. See also 9.4.3.

### 6.5 Design with strut and tie models

#### 6.5.1 General

(1)P Where a non-linear strain distribution exists (e.g. supports, near concentrated loads or plain stress) strut-and-tie models may be used (see also 5.6.4).

#### 6.5.2 Struts

(1) The design strength for a concrete strut in a region with transverse compressive stress or no transverse stress may be calculated from Expression (6.55) (see Figure 6.23).




Figure 6.23: Design strength of concrete struts without transverse tension

$$\sigma_{Rd,max} = f_{cd} \quad (6.55)$$

It may be appropriate to assume a higher design strength in regions where multi-axial compression exists.

(2) The design strength for concrete struts should be reduced in cracked compression zones and, unless a more rigorous approach is used, may be calculated from Expression (6.56) (see Figure 6.24).




Figure 6.24: Design strength of concrete struts with transverse tension

$$\sigma_{Rd,max} = 0,6 v f_{cd} \quad (6.56)$$

Note: The value of  $v$  for use in a Country may be found in its National Annex. The recommended value is given by equation (6.57N).

$$v = 1 - f_{ck}/250 \quad (6.57N)$$

(3) For struts between directly loaded areas, such as corbels or short deep beams, alternative calculation methods are given in 6.2.2 and 6.2.3.

#### 6.5.3 Ties

(1) The design strength of transverse ties and reinforcement should be limited in accordance with 3.2 and 3.3.

(2) Reinforcement should be adequately anchored in the nodes.

## EN 1992-1-1 (2004)

- Strut-and-tie oriented (D-regions)
- 4 pages
- Rules on strut, ties and nodes

107

Project NDP - working copy




# 1. Introduction

## Reasons for change [BD FprEN 1992-1-1:2023]

EN1992-1-1:2004 was inspired in Schlaich's approach to D-regions (1980s). Since then, many advances have been consolidated:

- analogies of strut-and-tie models with the stress field method




# 1. Introduction

## Reasons for change [BD FprEN 1992-1-1:2023]

EN1992-1-1:2004 was inspired in Schlaich's approach to D-regions (1980s). Since then, many advances have been consolidated:

- analogies of strut-and-tie models with the stress field method
- explicit consideration of the strain state in the calculation of efficiency factors




# 1. Introduction

## Reasons for change [BD FprEN 1992-1-1:2023]

EN1992-1-1:2004 was inspired in Schlaich's approach to D-regions (1980s). Since then, many advances have been consolidated:

- analogies of strut-and-tie models with the stress field method
- explicit consideration of the strain state in the calculation of efficiency factors
- integration of strut-and-tie models and stress fields within automated design procedures and consistency with design of B-regions




# 1. Introduction

## Reasons for change [BD FprEN 1992-1-1:2023]

EN1992-1-1:2004 was inspired in Schlaich's approach to D-regions (1980s). Since then, many advances have been consolidated:

- analogies of strut-and-tie models with the stress field method
- explicit consideration of the strain state in the calculation of efficiency factors
- integration of strut-and-tie models and stress fields within automated design procedures and consistency with design of B-regions

Revision of EN1992-1-1:2004 was based on updated state-of-the-art presented in Bulletin 100 of fib



# 1. Introduction

EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM

FINAL DRAFT  
FprEN 1992-1-1

April 2023

ICS 91.010.30; 91.080.40

Will supersede EN 1992-1-1:2004

English Version

## Eurocode 2 - Design of concrete structures - Part 1-1: General rules and rules for buildings, bridges and civil engineering structures

Eurocode 2 - Calcul des structures en béton - Partie 1  
1. Règles générales et règles pour les bâtiments, les  
ponts et les ouvrages de génie civil

Eurocode 2 - Bemessung und Konstruktion von  
Stahlbeton- und Spannbetonbauwerken - Teil 1.1:  
Allgemeine Regeln und Regeln für Hochbauten,  
Brücken und Ingenieurbauwerke

This draft European Standard is submitted to CEN members for formal vote. It has been drawn up by the Technical Committee CEN/TC 250.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

**Warning:** This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.




EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2023 CEN All rights of exploitation in any form and by any means reserved  
worldwide for CEN national Members.

Ref. No. FprEN 1992-1-1:2023 E



- a) control perimeters for radial arrangements ( $b_{s,s}$  and  $b_{s,i}$  refer to the instance of the 3<sup>rd</sup> perimeter of shear reinforcement)  
b) control perimeters for cruciform arrangements  
c) control perimeters for wall ends, wall corners, large and elongated columns (instance of wall end with radial arrangement of shear reinforcement)

### Key

- 1 supporting area

Figure 8.24 — Definition of control perimeters for punching reinforcement

## 8.5 Design with strut-and-tie models and stress fields

### 8.5.1 General

(1) Strut-and-tie models or stress fields should be used for design and verification of discontinuity regions (i.e. regions where the strain state distribution is not linear such as near concentrated loads or geometric discontinuities) in absence of specific provisions elsewhere in this code or of alternative refined analyses.

NOTE All provisions of 8.2.3 to 8.2.5 and 8.3 and Annex G are consistent with the rules given in 8.5. Linear members with shear reinforcement and without discontinuities can thus also be designed for bending, shear and torsion with the provisions of 8.5. Unless stated otherwise, the provisions in 8.5 apply to cases that can be modelled under plane stress conditions. Alternative and more refined verification methods for struts, ties and nodes can be adopted for special cases (e.g. where triaxial stress conditions apply).

(2) The provisions in 8.5 are applicable without a verification of the deformation capacity provided that the following conditions are fulfilled:


- the member contains a minimum reinforcement according to Clause 12 or the development of uncontrolled cracks is avoided by other means;
- the reinforcement complies with the details according to Clauses 11 and 12;
- the reinforcing steel is either ductility Class B or C.

## FprEN 1992-1-1 (2023)

- Strut-and-tie and stress fields oriented
- 9 pages
- Possibility to develop strut-and-tie models and/or stress fields consistently
- Consistent rules with shear design
- Methods to develop equilibrium based strut-and-tie models, rigid-plastic stress fields and more advanced (compatible) stress fields





## 2. Strut-and-tie and stress fields models



Ritter (1899)



## 2. Strut-and-tie and stress fields models



Drucker (1961)

## 2. Strut-and-tie and stress fields models

### Dimensionamiento y verificación del hormigón estructural mediante el método de los campos de tensiones

Dimensioning and check of structural concrete using the stress field method

Aurelio Muttoni

Prof. Dr., Ecole Polytechnique Fédérale de Lausanne, Suiza

Miguel Fernández Ruiz

Dr. Ecole Polytechnique Fédérale de Lausanne, Suiza

#### RESUMEN

Los campos de tensiones son una herramienta basada en el teorema del mínimo de la plasticidad que puede ser empleada tanto para el dimensionamiento como para la verificación de elementos o estructuras de hormigón armado y pretensado. En este artículo se resumen sus bases teóricas y de aplicación, presentándose finalmente un ejemplo del cual se analizaron los resultados obtenidos.

#### SUMMARY

The stress field method is a tool based on the lower-bound theorem of plasticity. It can be applied for both the dimensioning of new structural elements and for the checking of existing ones. This paper reviews the theoretical principles of the method and its application to practical cases. An example is finally presented whose results are discussed.


#### 1. INTRODUCCIÓN

El método de los campos de tensiones es una herramienta fundada en la teoría de la plasticidad que permite el dimensionamiento y verificación de elementos y estructuras de hormigón armado y pretensado. Su aplicación no se restringe exclusivamente a este ámbito, pudiendo ser empleado además en el análisis de estructuras en acero estructural o bien de fábrica (adobe y piedra).

Existen además otros métodos de cálculo basados en la teoría de la plasticidad con aplicación al hormigón estructural. Entre ellos destaca principalmente el método de las bielas y los tirantes, el cual se basa en la denominada analogía de la celosía y que ha sido adoptado en la norma española EHE. El análisis del hormigón estructural mediante modelos de celosía comenzó en un principio como un desarrollo intuitivo del comportamiento del hormigón armado, sin bases teóricas sólidas y sobre la base de resultados de ensayos. Ritter (1899) propuso por primera vez el análisis de una viga de hormigón armado mediante su idealización como una celosía. El desarrollo de modelos de celosía continuó posteriormente con Morsch (1908) y su evolución ha seguido hasta nuestros días. En esta línea, Schlaich (1982, 1987) completando diferentes aspectos teóricos y prácticos de la analogía de la celosía, formalizó un método de análisis y comprobación de estructuras, el cual ha sido ampliamente difundido y empleado bajo el nombre de método de las bielas y los tirantes.


Los campos de tensiones nacen en cambio como una aplicación directa de la teoría de la plasticidad. El primer planteamiento de un campo de tensiones completo para un elemento de un campo de tensiones finito para una viga bajo carga puntual y bajo carga distribuida. El desarrollo posterior de la aplicación de los campos de tensiones al estudio del hormigón estructural se produjo fundamentalmente en la ETHZ (Zürich) de la mano del profesor Thürlimann, continuando su evolución hasta nuestros días con diversos trabajos sobre el tema (Müller 1978, Martí, 1980, Muttoni 1980). Otro centro destacado en el desarrollo de esta técnica ha sido la universidad de

Investigaciones




## 2. Strut-and-tie and stress fields models

fib Bulletin 100  
CEB-FIP



Design and assessment with  
strut-and-tie models and stress fields:  
from simple calculations to detailed  
numerical analysis


State-of-the-art report



### 3. Compression fields and struts

Action:

$$\sigma_{cd} = \frac{|F_{cd}|}{b_c \cdot t}$$




### 3. Compression fields and struts

Action:

$$\sigma_{cd} = \frac{|F_{cd}|}{b_c \cdot t}$$

Resistance:

$$\sigma_{cd} \leq \nu \cdot f_{cd}$$




Plastic strength

(Muttoni, 1990)

$$f_{cd} = \eta_{cc} \cdot k_{tc} \frac{f_{ck}}{\gamma_C}$$

$$\eta_{cc} = \left( \frac{f_{ck,ref}}{f_{ck}} \right)^{\frac{1}{3}} \leq 1,0$$



Compression softening

(Robinson and Démorieux, 1962)

(Vecchio and Collins, 1986)


### 3. Compression fields and struts

Action:


$$\sigma_{cd} = \frac{|F_{cd}|}{b_c \cdot t}$$

Resistance:

$$\sigma_{cd} \leq v \cdot f_{cd}$$



$$v = \frac{1}{1,0 + 110\varepsilon_1} \leq 1,0$$




### 3. Compression fields and struts

Action:



$$\sigma_{cd} = \frac{|F_{cd}|}{b_c \cdot t}$$

Resistance:

$$\sigma_{cd} \leq v \cdot f_{cd}$$




$$v = \frac{1}{1,0 + 110\varepsilon_1} \leq 1,0$$



$$\varepsilon_x \approx \varepsilon_{yield} / 2 \approx 0.001$$

$$v = \frac{1}{1,11 + 0,22 \cdot \cot^2 \theta_{CS}}$$

(but  $\varepsilon_x$  might have other values for panels with for instance uniform strain level)



$$\varepsilon_1 = \varepsilon_x + (\varepsilon_x + 0.001) \cdot \cot^2 \theta$$




### 3. Compression fields and struts

Action:


$$\sigma_{cd} = \frac{|F_{cd}|}{b_c \cdot t}$$

Resistance:

$$\sigma_{cd} \leq v \cdot f_{cd}$$



$$v = \frac{1}{1,0 + 110\varepsilon_1} \leq 1,0$$




Eq. (8.119) (Eq. (8.121) considering  $\varepsilon_1 = \varepsilon_x + (\varepsilon_x + 0.001) \cot^2 \theta$ , with  $\varepsilon_x = 0.001$ )  
Constant values §8.5.2(4)

$$v = \frac{1}{1,11 + 0,22 \cdot \cot^2 \theta_{cs}}$$



## 4. Nodal regions


CCC




No need for detailed checks,  $v$   
is governed by strut conditions

## 4. Nodal regions

CCC




CCT




## 4. Nodal regions


CTT




a) strut-and-tie model and equilibrium of forces



b) strut-and-tie model and stress field for the deviation force of a bent bar




c) strut-and-tie model and stress field for anchorages outside the node




d) strut-and-tie model and stress field for anchorages inside the node with deviations occurring due to bond

## 4. Nodal regions


CTT




a) strut-and-tie model and equilibrium of forces



b) strut-and-tie model and stress field for the deviation force of a bent bar



c) strut-and-tie model and stress field for anchorages outside the node



d) strut-and-tie model and stress field for anchorages inside the node with deviations occurring due to bond

TTT



TTT nodes, where only ties reach the node. TTT nodes may be used only if consistent values of the strength reduction factor  $\nu$  in the node are adopted accounting for anchorage, detailing and strains according to 8.5.2(5).

## 5. Example of application

- Existing school at Lausanne (Switzerland)
- Refurbishment works, including a new courtyard
- Engineer: Antonio Garcia (Muttoni et Fernández, ingénieurs conseils SA)




## 5. Example of application




## 5. Example of application


- Span length  $L = 12.1$  m
- Main girders  $b = 50$  cm
- Unusual shape of the support
- Heavily reinforced in bending
- How to approach a suitable detailing for the support region?




## 5. Example of application





## 5. Example of application




## 5. Example of application



## 5. Example of application



## 5. Example of application



**Thank you for your attention**

Miguel Fernández Ruiz





## 2. Strut-and-tie and stress fields models

- Minimum reinforcement amount for crack control



Campana et al. (2008)




Rupf et al. (2012)

- Reinforcement: ductility class B or C


## 5. Special cases

### Spreading of concentrated forces



$$\tan\theta_{cf} = \frac{1 - a/b}{2}$$

### Forces at edges of walls



$$\tan\theta_{cf} \geq 1/4$$

## Contents

1. <Name of Item 1>
  - 1.1. <Name of Subitem 1.1>
  - 1.2. <Name of Subitem 1.2>
2. <Name of Item 2>
3. <Name of Item 3>
4. <Name of Item 4>
5. <...>



# 1. <Name of Item 1>

## LEVEL 1:

- LEVEL 2
- LEVEL 3

## LEVEL 1:

- LEVEL 2
- LEVEL 3

## LEVEL 1:

- ...

